

IITDh/IPS/2025-26/LPC/127
25th Aug 2025

Invitation for Quotation

Name of the Work: Aluminum Partition and Playground Work

Location: Creche Facility at Housing Gate Security Lounge.

With reference to the aforementioned work, quotations are hereby invited for the said work. Interested vendors with experience in said works can submit their quotes (*as per Annexure-I*) on their official letterhead, duly attested, **in a sealed envelope via post / courier** to the following address:

To,
IPS Office (NE-113),
First Floor Admin Block,
Indian Institute of Technology Dharwad,
Permanent Campus, Chikmalligwad.
Dharwad-580011.

Deadline for submission: 08th September 2025 up to 1300 hours

NOTE:

- Any quotes received after 1300 hours on 08/09/2025 will not be accepted.
- Name of the Work / LPC number and Firm name should be mandatorily written on the sealed cover.

Sd/-
Executive Engineer
Indian Institute of Technology Dharwad

Annexure-I

BoQ for Aluminium Partition and Playground Work

Sl. No.	Description	Unit	Qty.	Rate (₹)	Amount (₹)
1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling to be paid for separately) For fixed portion Polyester powder coated aluminium (minimum thickness of polyester powder coating 50 micron)	Kg	92.23		
2	Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in- charge. Pre-laminated particle board with decorative lamination on both sides	Sqm	29.45		

3	Filling the gap in between aluminium/ stone/ wood frame and adjacent RCC/Brick/ Stone/ wood/ Ceramic/ Gypsum work by providing weather/structural non sag elastomeric PU sealant over backer rod of approved quality as per architectural drawings and direction of Engineer-in-charge complete, complying to ASTM C920, DIN 18540- F & ISO 11600 Upto 5 mm depth and 5 mm width	Rmt	30.20		
4	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Polyester powder coated aluminium (minimum thickness of polyester powder coating 50 micron)	Kg	10.25		

5	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item):With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm)	Sqm	4.62		
6	Providing and fixing Brass 100mm mortice latch and lock with 6 levers without pair of handles (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.	Nos	1.00		
7	Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete : 200 mm	Nos	2.00		
8	Aluminum Sliding Door - Precision Roller System: Door dimensions are 1.0m x 2.1m. Supply, installation, testing, and commissioning of a sliding door precision roller system, which includes the track channel and rollers designed to support the total load according to site conditions. The work should be completed under the guidance of the Engineer-In-Charge. Approved brands such as Hettich, Hafele, Ozone, or others approved by the Engineer-In-Charge should be used.	Nos	1.00		
9	Providing and Fixing frosted glass film to the glass surface in accordance with the required pattern, along with any necessary fixing, shall be completed as per the instructions of the Engineer-in-Charge. For payment purposes, only the area of application will be measured.	Sqm	56.13		
10	Surface dressing of the ground including removing vegetation and inequalities not exceeding 15 cm deep and disposal of rubbish, lead up to 50 m and lift upto 1.5	Sqm	420.00		

	m. All kinds of soil.				
11	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:3:6 (1 Cement : 3 coarse sand(zone-III) derived from natural sources : 6 graded stone aggregate 20 mm nominal size derived from natural sources).	Cum	0.95		
12	Providing and laying at or near ground level factory made kerb stone of M-25 grade cement concrete in position to the required line, level and curvature, jointed with cement mortar 1:3 (1 cement: 3 coarse sand), including making joints with or without grooves (thickness of joints except at sharp curve shall not to more than 5mm), including making drainage opening wherever required complete etc. as per direction of Engineer-in-charge (length of finished kerb edging shall be measured for payment). (Precast C.C. kerb stone shall be approved by Engineer-in-charge).	Cum	4.26		
TOTAL					
GST					
GRAND TOTAL					

(Contractors Sign and Seal)